



F68 Android POS Machine with 58 mm. Thermal Printer



15.6" Single Screen



15.6"+15.6" Dual Screen

The best choice for industries such as advertising machines and self-service terminals.



Build-in 58mm. Thermal Printer



15.6" Large Touch Screen



SUPERMARKET



BAKERY



MANAGEMENT



CLOTHING SHOP



RESTAURANT



SHOPPING MALL

Specification

Mainboard

Operation system	Android 11
CPU	Rockchip RK3568 quad-core 2.0 GHz. processor, with 1.0T computing power NPU.
RAM	2GB RAM DDR4 + 32GB ROM EMMC
Speaker	3W speaker

Connection I/O Port

Power	DC-IN
LAN	1X RJ45 10/100M
Cash Drawer	1X RJ11 Cash Drawer (Support Loyverse)
Serial Port	1X RS232 / 1X RJ12
USB	4X USB 2.0 / 2X USB 3.0
Audio	1X 3.5 mm. Audio Jack
SD Card	-none-

Wireless Connection

WiFi	Support IEEE 802.11a/b/g/n wireless protocol 2.4G (standard)
Bluetooth	BT 2.1/3.0/4.0/4.2

Main Screen

Size	15.6"
Resolution	1366 x 768
Touch Screen	10 points touch capacitive screen

Customer Screen

Size	15.6"
Resolution	1366 x 768
Touch Screen	10 points touch capacitive screen

Build-in 80 mm. Thermal Printer

Paper Width	58 mm. (55 mm. Print Area)
Paper Roll	60 mm.
Resolution	200 DPI
Density	300 Dot/Line
Print Speed	160 mm./s
Printable Content	GBK Chinese character library, ASCII characters, one-dimensional barcode, support different density point map, raster bitmap and download bitmap printing. Scalable 2D barcodes.
Default Font	9X17 (ASCII), 24x24 (Chinese)
Cutter Life	1,000,000. Cut
Barcode Support	UPC-A, UPC-E, EAN-13, EAN-8, CODE39, ITF25, CODABAR, CODE93, CODE128, PDF417, QR Code, DATAMatrix


Media Support

Image	BMP , JPEG , PNG , GIF , etc...
Video	4K 60fps H.265/H.264/VP9 video decoding, support 1080P 100fps H.265/H.264
Audio	MP3 , WMA , APE , Flac , etc...

Other

Power	12V DC 5A
Operation Temperature	-0 ~ 60 °C
Storage Temperature	-20 ~ 70 °C
Hummidity	<80%

Connection I/O Port



DC-IN



1X CASH DRAWER




1X RJ11



4X USB 2.0



2X USB 3.0



AUDIO



1X LAN



F68 Android POS Machine with 80 mm. Thermal Printer



15.6" Single Screen



15.6"+15.6" Dual Screen

The best choice for industries such as advertising machines and self-service terminals.



Build-in 80mm. Thermal Printer



15.6" Large Touch Screen



SUPERMARKET



BAKERY



MANAGEMENT



CLOTHING SHOP



RESTAURANT




SHOPPING MALL

Specification

Mainboard	
Operation system	Android 11
CPU	Rockchip RK3568 quad-core 2.0 GHz. processor, with 1.0T computing power NPU.
RAM	2GB RAM DDR4 + 32GB ROM EMMC
Speaker	3W speaker
Connection I/O Port	
Power	DC-IN
LAN	1X RJ45 10/100M
Cash Drawer	1X RJ11 Cash Drawer (Support Loyverse)
Serial Port	1X RS232 / 1X RJ11
USB	4X USB 2.0 / 2X USB 3.0
Audio	1X 3.5 mm. Audio Jack
SD Card	-none-
Wireless Connection	
WiFi	Support IEEE 802.11a/b/g/n wireless protocol 2.4G (standard)
Bluetooth	BT 2.1/3.0/4.0/4.2
Main Screen	
Size	15.6"
Resolution	1366 x 768
Touch Screen	10 points touch capacitive screen
Customer Screen	
Size	15.6
Resolution	1366 x 768
Touch Screen	10 points touch capacitive screen
Build-in 80 mm. Thermal Printer	
Paper Width	82 mm. (79 mm. Print Area)
Paper Roll	80 mm.
Resolution	203 DPI
Density	636 Dot/Line
Print Speed	250 mm./s
Printable Content	GBK Chinese character library, ASCII characters, one-dimensional barcode, support different density point map, raster bitmap and download bitmap printing. Scalable 2D barcodes.
Default Font	9X17 (ASCII), 24x24 (Chinese)
Cutter Life	1,000,000. Cut
Barcode Support	UPC-A, UPC-E, EAN-13, EAN-8, CODE39, ITF25, CODABAR, CODE93, CODE128, PDF417, QR Code, DATAMatrix
Media Support	
Image	BMP , JPEG , PNG , GIF , etc...
Video	4K 60fps H.265/H.264/VP9 video decoding, support 1080P 100fps H.265/H.264
Audio	MP3 , WMA , APE , Flac , etc...
Other	
Power	12V DC 5A
Operation Temperature	-0 ~ 60 °C
Storage Temperature	-20 ~ 70 °C
Hummidity	<80%

Connection I/O Port



DC-IN



1X CASH DRAWER




1X RJ11



4X USB 2.0



2X USB 3.0



AUDIO



1X LAN

MYPOS Technology (Thailand) Co., Ltd.

49/293 Soi Vibhavadi-Rangsit 64 Yeak 13,

Talat Bangkhen, Lak Si, Bangkok 10210

Tel: +66-2-521-7155 ~ 59

Fax: +66-2-521-7167

Email: sales@myposthai.com