



## Thermal Receipt Printer

# F-8220

- High speed printing up to 300 mm/second
- Up to 100 mm print head
- Low power consumption
- No ribbon or ink cartridges
- Easy to operate
- Suitable for all type of commercial retail
- Support NV and logo, QR-Code, Cash drawer
- Support multilanguage printing
- Support android and PC POS system
- Full-Partial Cutting
- Compatible with ESC/POS
- High quality auto-cutter
- Paper jamming problem free
- Support interface  
USB / USB + LAN / USB + COM + LAN  
/ USB + WIFI / USB + Bluetooth



# F-8220

## Thermal Receipt Printer



<b>Printing</b>	Printing method	Thermal dot line
	Print width	72 ± 0.5 mm
	Reliability	100 km
	Print speed	300 mm/s
	Interface type	USB / Serial / Parallel / LAN / WIFI / Bluetooth (Optional)
	Print command	ESC/POS
	Paper roll diameter	83 mm
	Paper thickness	0.06-0.08 mm
	Print Character	576 dots/line , 512 dots/line , ANK Character Font A : 12x24 dots (1.5x3.0 mm) Font B : 9x17 dots (1.1x2.1 mm) Simplified/Traditional Chinese 24x24 dots (3.0x3.0 mm)
<b>Power</b>	Cash drawer	12 VDC / 1 A
	Adapter	Input : 220 VAC 50-60 Hz / Output : 24 VDC 2.5 A
<b>Physical Properties</b>	Weight	2.3 kg (include accessories)
	Diomension	18.6 x 14.5 x 14 cm
<b>Environment</b>	Working temperature	0 - 45 °C
	Working humidity	10% - 80% RH
<b>Paper cutter</b>	Auto cut / Full-Partial cut	
<b>Barcode</b>	UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODEBAR / ITF / CODE93 / CODE128	
<b>Driver</b>	Win 9x , 2000 , 2003 , XP , Vista , 7 , 8 , 10 / Linux / Android	
<b>Certificates</b>	CF / FCC / CCC	