




# High Speed Thermal Printer

# P-58

Model	P58-BT	P58-WiFi	P58-4G	P58-4GWF
				
Print Speed	90 mm/s	90 mm/s	90 mm/s	90 mm/s
Paper Width	58 mm	58 mm	58 mm	58 mm
Connection	USB + BT	USB + WiFi	USB + 4G	USB + WiFi + 4G
Real Voice	Support	Support	Support	Support
Cloud Printing	Not Support	Not Support	Not Support	Not Support
Portable Print	Support	Support	Support	Support

## Specification

Model	P58
SIZE	116 x 116 x 117 mm
Weight(g)	500g (not including the paper roll)
Print method	Line thermal printer
Paper width	57 mm.
Max diameter of paper roll	60 mm.
Paper thickness	0.12 mm.
Dot per line	384 dots/line
Internal characters	ASCII(8x16.9x179x2412*24)GB18030(16x1624*24)
Print speed	90mm/s
Life cycle time	50 km (print density under 12.5%)/100 million pulses
Text and graphic Support	Support English, figuresymbol, Chinese graph curve icon pre-stored barcode (CODE39, EAN13, EAN8, CODABAR, CODE128, CODE93, ITF, QR code, PDF417)
Dot pitch (resolution)	203DP1/8 dots/mm
Interface (Optional)	USB+BT / USB+WiFi / USB+4G / USB+4G+WiFi
Recharge adapter	Stand by recharging/AC adapter
Self-check	Without paper/cover open
Paper feeding	Easy paper loading
Commands	ESC/POS compatible with order sets
Paper cut	By hands
Operate setting	Temperature -10°C~50°C ; Humidity 20%~85%
Recharge Setting	Temperature 5°C~40°C ; Humidity 20%~85%
Storage Setting	Temperature -20°C~70°C ; Humidity 5%~95%
Standard accessories	Long-term preservable paper, AC adapter, li-ion battery, USB cable
Color	Black / White

