P-8025 80 mm. Thermal Printer

MYPOS

MYPOS

Compact 80mm Thermal Printer

Printing width	80	mm.
Density	640	dots/line
Print speed	250	mm/sec
Resolution	203	DPI

Specification

Printing	
Print Method	Thermal line printing
Printing width	80mm
Dot density	640 dots/line
Print speed	250mm/sec
Print Resolution	203x203DPI
I/O interface	Serial port + USB + Ethernet port
Print paper	Paper width 79.5 ±0.5mm / Paper Roll Diameter 100mm
Leading	3.75mm (Adjustable)
Print Font	Font A: 42 x 48 dots, Font B: 56 x 64 dots Chinese Character: 21 x 24 dots
Character	GB180030 Simplified Chinese
Character size	ANK Font Font A 1.5×3.0mm (12×24 dots) Font B 1.1×2.1mm (9×17 dots) Simplified/Traditional Chinese 3.0×3.0mm(24×24 dots)

Barcode character	
Extended character list	PC437/Katakana/PC850/PC860/PC863/PC865/ West Europe (PT151,1251)/(WPC1257)/(PC864)/ (Vietnam)/(Thai)
Barcode type	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8) CODE39/ITF/CODABAR/CODE93/CODE128

Buffer	
Receipt	128 Kbytes
NV Flash	256 Kbytes

Power	
Cash drawer	DC 24V/1A
Power adapter	DC 24V/2A
Power supply	Input : AC 110V/220V, 50 ~ 60Hz Output : DC 24/2A

Package	
Weight	1.90 KG
Size	175 x 138 x 124 mm.

Environment	
Operating environment	Temperature : 5 ~ 45 °C Humidity : 10 ~ 80%
Storage environment	Temperature : -10 ~ 50 °C Humidity : 10 ~ 90%

Print Life	
Print head lifetime	150 Km
Cutter lifetime (Cuts)	1.5 million times

MYPOS

MYPOS Technology (Thailand) Co., Ltd.
49/293 Soi Vibhavadi-Rangsit 64 Yeak 13,
Talat Bangkhen, Lak Si, Bangkok 10210
Tel: +66-2-521-7155 ~ 59
Fax: +66-2-521-7167
Email: sales@myposthai.com