



Wall-Mounted



K156A Specification



Single Screen

- Main Screen 15.6" 1366x768 Multi-Touch
- CPU RK3568



Dual Screen

- Main Screen 15.6" 1366x768 Multi-Touch
- 2nd Screen 15.6" 1366x768
- CPU RK3568

OS Operating System

Android 9 (RK3288)
Android 11 (RK3568)



Connection

IEEE802.11 b/g/n
Bluetooth 4.0 BLE



Color

Body Color
White or Black



Card Slot

1x SIM Card
1x TF Card



Scanner

1D&2D Scanner
Barcode, QR-Code



Power

DC 12V 5A



CPU/Memory Configuration Standard

RK3568 Quad-core 2.0 GHz,
2GB RAM + 32GB Storage

Option 1

RK3568 Quad-core 2.0 GHz,
4GB RAM + 32GB Storage

Option 2

RK3288 Quad-core 1.8 GHz,
2GB RAM + 16GB Storage



Printer

80mm. Thermal Printer
Print speed 150 mm/s
Print head life 100 km
Cutter Life 1,000,000 cuts
Paper roll diameter 80 mm (MAX)



Display

Dual-Screen

- Main Screen 21.5" 1920x1080 | IPS | Capacitive Touch
Tilting Angle 35-90 Degree | Brightness 250 nits
- 2nd Screen 15.6" 1366x768

Single Screen

- Main Screen 21.5" 1920x1080 IPS



I/O and Interface

1x COM | 5x USB 2.0 (External)
2x USB 2.0 (Internal reserved for touch screen, MSR)
1x RJ45 Self-Adaptive 10/100 Ethernet
1x RJ11 | 1x Audio line out | 1x MIC | 1x Internal Speaker



Work Temp

Operating 0°C~50°C | Storage 0°C~70°C
Humidity: 10%~80% (Non-condensing)

Please Note :

1. Maximum RAM/Storage can be config base on CPU selection.
2. Details are subject to change without prior notice.

MYPOS Technology (Thailand) Co., Ltd.

49/293 Soi Vibhavadi-Rangsit 64 Yeak 13,
Talat Bangkhen, Lak Si, Bangkok 10210

Tel: +66-2-521-7155 ~ 59

Fax: +66-2-521-7167

Email: sales@myposthai.com